



Akron Brass Cord Reels are the ultimate in managing portable power cords. The Cord Reel allows for fast, easy deployment and retraction of extension cords without the hassle of twisting or knotting. Akron Cord Reels are available in Live and Non-Live configurations.

- All live reels are internally grounded
- Available in 3 sizes 10", 15" & 18"
- Heavy-duty construction
- Powder coated
- Live slip ring design
- Adjustable tension nut
- 6' direct wire pigtail (10/3 Black)
- Meets NFPA requirements



ECR-MT
Cord Reel
mounting brackets

ECR-15
15" Cord Reel with
optional yellow
cord



ECR-10-GB
10" Live Cord Reel with
gang box



Additional Options

- NEMA configuration connectors
- Heavy-duty cord & connectors (custom lengths)
- ECR-MT Cord Reel Mounting Bracket

ECR-18, ECR-15, & ECR-10 are live cord reels allowing continuous power to the cord as it is deployed or retracted while providing excellent storage and organization of extension cords.

NCR-18, NCR-15, & NCR-10 are non-live cord reels providing excellent storage and organization of extension cords.

NCR-18-GB, NCR-15-GB, & NCR-10-GB are non-live cord reels with a gang box permanently mounted to the reel. Simply plug the cord into a receptacle and carry the reel to the fire ground or work site.

ECR-18-GB, ECR-15-GB, & ECR-10-GB are live cord reels with a gang box permanently mounted to the axle. Simply plug the cord into a receptacle and carry the reel to the fire ground or work site.

NCR-18-LH, NCR-15-LH, and NCR-10-LH are non-live cord reels, designed to be used as a live reel. Simply unwind as much cord as needed while still having the capabilities of plugging the cord in. The "L" hooks allow for the pigtail to be secured while the reel is being turned.

Cord Reel Lights are reverse wired live cord reels, which allows a plug on the cord to be plugged into a power source while the Cord Reel Light is carried to the fire ground or work site. The Cord Reel Light allows the scene to be illuminated while providing a receptacle for additional tools or lights. Akron Brass' Cord Reel Lights come in several variations with either 500 or 750 Watt low profile Beta Light heads.

Improved
tilt angle

LED Indicator
Light

On/Off Light
Switch

Nonslip Feet

ECR-10-4500
10" Cord Reel
Light with
optional
yellow cord



NCR-18
18" Non-Live Cord
Reel



18" Cord Reel

15" Cord Reel

10" Cord Reel



Cord Reel Lights

P/N	Description
ECR-10-4500	10" (254 mm) Live Cord Reel with Beta 4500 Light and Gang Box
ECR-10-4750	10" (254 mm) Live Cord Reel with Beta 4750 Light and Gang Box
ECR-15-4500	15" (381 mm) Live Cord Reel with Beta 4500 Light and Gang Box
ECR-15-4750	15" (381 mm) Live Cord Reel with Beta 4750 Light and Gang Box
ECR-18-4500	18" (457 mm) Live Cord Reel with Beta 4500 Light and Gang Box
ECR-18-4750	18" (457 mm) Live Cord Reel with Beta 4750 Light and Gang Box

Cord Type	10" Cord Reel Capacity	Weight W/cord	15" Cord Reel Capacity	Weight W/cord	18" Cord Reel Capacity	Weight W/cord
14/3-300 Volt	150' (45.7 m)	22# (10 kg)	300' (91.5 m)	46# (20.1 kg)	450' (137 m)	61# (27.7 kg)
12/3-300 Volt	100' (30.5 m)	22# (10 kg)	200' (61 m)	46# (20.1 kg)	300' (91.5 m)	61# (27.7 kg)
10/3-300 Volt	N/A	N/A	100' (30.5 m)	42# (19 kg)	175' (53.3 m)	60# (27.2 kg)
14/3-600 Volt	50 (15.2 m)	17# (7.7 kg)	125' (38 m)	37# (16.8 kg)	225' (68.7 m)	54# (24.5 kg)
12/3-600 Volt	N/A	N/A	100' (30.5 m)	41# (18.6 kg)	150' (46 m)	54# (24.5 kg)
10/3-600 Volt	N/A	N/A	75' (22.8 m)	40# (18.1 kg)	100' (30.5 m)	49# (22.3 kg)
10/4-600 Volt	N/A	N/A	N/A	N/A	100' (30.5 m)	50# (22.7 kg)

NCR-18-GB
18" Non-Live
Cord Reel with
a gang box

