

Apparatus Flow Test Kit

FK-25

- Apparatus flow test kits include your choice of four (4) out of the nine (9) tips offered. Tips range from 3/4" to 2 1/2" in 1/8" increments
- Standard with 1 1/2", 1 3/4", 2", 2 1/4" tips (3/4", 1", 1 1/8", 1 1/4", 2 1/2" tips optional) - Must specify
- 3 1/2" liquid filled 0-160 psi gauge
- Large, heavy duty carrying case (FK-230), 18 3/8" W x 14 1/4" D x 8" H
- 2 1/2" female swivel
- Certified calibrated gauges
- Large diameter flow test tips available



FK-25



Apparatus Test Gauge Kit

TGK-2

- 36" test hoses, connect directly to underwriter's test fittings (Style 44)
- ±1% accurate, 3 1/2" diameter, freeze protected liquid filled gauges
- 0-30", .5Hg increment vacuum and 0-300, 5 psi increment pressure gauges
- Heavy-duty carrying case
- Certified calibrated gauges



TGK-2



TGK-3

TGK-3

- Same as TGK-2 with a space for an extra gauge to be mounted (Requires RG-230 remote assembly)

Pressure/Vacuum Panel Adapter

44

Pressure/Vacuum Panel Adapter

- Complete fitting for pump panel
- Simplifies attachment of gauges for pump tests
- Remove hex plugs and screw in gauges
- Length: 3 1/2", height: 1 3/8", weight: 8 oz.



Style 44

Line Gauges

- Designed to determine nozzle pressure and static pressure
- 3 1/2" freeze protected liquid filled 0-160 psi (0-1100 kpa)

35

Line Gauge

- Ideal for use in high-rise packs
- Available in 2 1/2" and 3" sizes
- 1 1/2" diameter peanut gauge (0-300) with guard
- Grade B 3%-2%-3% accuracy
- 2 1/2" weight: 2 lbs., length: 5"
- 3" weight: 2 1/2 lbs., length: 5 1/2"
- Certified calibrated gauges
- Pyrolite® construction

Style	Description	Description
LG-15	1 1/2" (38 mm)	Line Gauge
LG-25	2 1/2" (65 mm)	Line Gauge
LG-30	3" (75 mm)	Line Gauge
LG-35	3 1/2" (89 mm)	Line Gauge
LG-40	4" (100 mm)	Line Gauge
LG-45	4 1/2" (114 mm)	Line Gauge
LG-50	5" (125 mm)	Line Gauge
LG-60	6" (150 mm)	Line Gauge



LG-25



Style 35

Cap Gauge

- Certified calibrated gauges
- Designed for determining the static pressure of water in fire hydrants, fire hoses, and/or fire pumps
- 3 1/2" liquid filled 0-160 psi (0-1100 kpa) gauge, 2 p.s.i. (20 kpa) increments, ±1% accurate full scale
- Pyrolite® construction

Style	Description
CG-15	1 1/2" (38 mm) NH Cap Gauge
CG-25	2 1/2" (65 mm) NH Cap Gauge
CG-30	3" (75 mm) NH Cap Gauge
CG-35	3 1/2" (89 mm) NH Cap Gauge
CG-40	4" (100 mm) NH Cap Gauge
CG-40S	4" (100 mm) Storz Cap Gauge

Style	Description
CG-45	4 1/2" (114 mm) NH Cap Gauge
CG-50	5" (125 mm) NH Cap Gauge
CG-50S	5" (125 mm) Storz Cap Gauge
CG-60	6" (150 mm) NH Cap Gauge
CG-60S	6" (150 mm) Storz Cap Gauge



CG-25

