

Hose & Apparatus Test Equipment

The Hose Tester

HT-15-C

A fast, easy, safe way to test fire hose.

- Reduces the number of personnel required to test hose
- Reduces noise levels while testing
- Keeps apparatus in-service
- Prevents unnecessary wear and tear on engines, fire pumps, and transmissions resulting from static loads required by NFPA standards
- Low water flow virtually eliminates hazard of a wild, uncontrollable, ruptured hose line at test pressures
- Test any and all hose sizes with proper adapters
- 1 1/2" valves and piping
- 1 1/2" female swivel and four 2 1/2" male discharges. (3/4" garden hose thread inlet - optional)
- Pressure Washer System - optional



HT-15-C

Bleeder Caps

- Allows for proper air & water release from hoses being tested.
- Does not tie up a nozzle for hose testing leaving the truck in service.
- Improves safety of hose testing.

Style	Description	Style	Description
BC-15	1 1/2" Bleeder Cap	BC-45	4 1/2" Bleeder Cap
BC-25	2 1/2" Bleeder Cap	BC-50	5" Bleeder Cap
BC-30	3" Bleeder Cap	BC-50S	5" Storz Bleeder Cap
BC-35	3 1/2" Bleeder Cap	BC-60	6" Bleeder Cap
BC-40	4" Bleeder Cap	BC-60S	6" Storz Bleeder Cap
BC-40S	4" Storz Bleeder Cap		



BC-25

Gas Powered Hose Tester

GHT-15

The Gas Powered Hose Tester is designed for easy operation and long lasting service, this hose tester matches a 5.5 horsepower gasoline engine with a 1500 psi pump for optimum performance. With its narrow framework, it can be easily transported through doorway's, yet is stable enough to connect up to 4 each 5" Storz adapters directly to the manifold without tipping over the unit.

- Weight: 140 lbs.
- Size: 26" wide x 37" long x 24" tall
- Hydro 1500 psi, 3 gpm
Powerline Plus duplex oil bath plunger pump
- 1-1/2" NH inlet, 2-1/2" NH discharges (additional adapters available)
- 316 stainless steel manifold, pressure fittings and ball valves rated at 2000 psi
- Large 4" diameter 2000 psi Gauge
- Thermal relief valve
- Powder coated heavy duty steel frame with folding handles
- Solid rubber wheels
- Pressure washer wand & 50' hose assembly - Optional
- Tool & adapter storage basket - Optional
- Spanner wrench set & bracket - Optional



GHT-15
*Shown with optional Basket (TLBX)



Hose Test Valve

2285 Hose Tester Gate Valve

Meets NFPA 1962 requirements for testing hose with fire apparatus. Includes 1/4" hole in gate for maintaining test pressure at low volume.

Style 2285
Hose Gate Valve

Style	Material	Size	Length	Weight lbs. (kg)	Inlet	Outlet	Number Of Turns
2285	Pyrolite	2 1/2" (64 mm)	5 1/2" (140 mm)	4 (1.8 kg)	2 1/2" (64 mm)	2 1/2" (64 mm)	21

