



NOTE:
 ANY COLORED SHIMS FOUND UNDER THE BAFFLE HEAD SHOULD ALWAYS REMAIN WITH THE NOZZLE.

OPERATING INSTRUCTIONS:
 - FLOW RATE AT 100PSI (7 bar) OR 75PSI (5 BAR)
 - OPEN AND CLOSE SLOWLY
 - MAXIMUM OPERATING PRESSURE 230PSI (14 BAR)

ASSEMBLY NOTES:
 USE PARKER-O-LUBE ON ALL O-RINGS AND ALL MATING SURFACES.

- ① USE PERMABOND LM113 OR LOCTITE 222.
- ② USE LOW TEMP LUBRIPLATE.
- ③ DIMPLE AT ASSEMBLY.
- ④ DO NOT CUT TURBINE TEETH.
- ⑤ TIGHTEN SCREW.
- ⑥ RAISED LUG IN LINE WITH STRAIGHT STREAM.
- ⑦ AS SPECIFIED.
- ⑧ USED WHEN PISTOL GRIP IS NOT INSTALLED.



TECHNICAL SERVICE PARTS

STYLE 1763

PRODUCT WIDE-RANGE TBJT

IF AN ITEM IS NOTED AS "NOT FIELD REPAIRABLE", OR YOU WISH TO RETURN AN ITEM TO AKRON BRASS FOR SERVICE PLEASE GO ONLINE TO, **ONLINEREPAIR.AKRONBRASS.COM**

Chg.	Date
02	07-19
03	11-19

Find		Description	Item	QTY A
4		O-RING 2-132	757268	1
5	A	SEAT	769243	2
6		TRUNNION	127178	2
7	A	O-RING 2-111	757269	2
8	A,C	PIN ROLL 1/8" x 1-1/4"	744062	2
9	A	BALL 2.5"	704029	1
10		INSERT CAM	124270	1
11		SCREW ALLEN HEAD CUP POINT SET 1/4-20 x 1/4"	765002	2
14		SCREW SOCKET HEAD FULL DOG SET 10-24 x 5/16"	767088	1
15		BAND GALLONAGE CONTROL LPM	803350	1
15		BAND GALLONAGE CONTROL GPM	803349	1
16		O-RING 2-028	757341	1
17		AXLE CAM	702245	1
18		ROLLER CAM LONG	758356	1
19		ROLLER CAM SHORT	758226	1
22		BUMPER/PATTERN SLEEVE S/A	17634007	1
23		TUBE DISCHARGE 100 PSI	127263	1
23		TUBE DISCHARGE 75 PSI	127335	1
24	A	O-RING 2-140	757265	2
25		O-RING 2-036	757309	1
26		RING RETAINING	758354	1
27		SCREW SOCKET HEAD CAP #4-40 x 5/8"	767094	2
28		TEETH TURBINE	772153	1
29		HEAD BAFFLE 75P@5b/500kPa	127268	1
29		HEAD BAFFLE 100P@7b/700kPa	127267	1
30		SCREW SOCKET BUTTON HEAD 1/4-20 x 1"	765182	1
31	*	SHIM BLUE	-	1
33		NOZZLE BODY S/A	17634006	-
34		BALL STAINLESS STEEL 3/16"	704018	1

Find		Description	Item	QTY A
35		KEY DISCHARGE	727033	1
36		SPRING DETENT	769111	1
37		RING GALLONAGE CONTROL	109108	1
38		BAND PATTERN INDICATOR 1763	803351	1
39		SPACER	769799	1
40		BODY SHUTOFF 1763	127261	1
42		SWIVEL 1.50"NH	45154001	1
42		SWIVEL 1.50"BSP	45154003	1
42		SWIVEL 1.50"NPSH	45154002	1
44	C	HANDLE SHUTOFF	721761	1
46	A	GASKET	717042	1
50		RING PATTERN SLEEVE	127265	1
52	*	SHIM BROWN	-	1
53	*	SHIM PINK	-	1
54	*	SHIM GREEN	-	1
56		O-RING 2-032	757447	1
61		O-RING 2-129	757308	1
62		SCREW SOCKET HEAD CUP POINT SET 5/16-18 X 1/4"	765071	1
74		O-RING 2-132	757422	2
75	B	GRIP PISTOL	718330	1
76	B	SCREW SOCKET HEAD CAP 5/16-18 x 2-3/4"	765397	1
77	B	WASHER LOCK HEAVY DUTY 5/16 ST STL USA	784090	1
80	B	WASHER FLAT 5/16"	784093	1
99		LABEL FM	729669	1
81		SPACER (75 PSI ONLY)	769388	1
A		FIELD SERVICE KIT	91790001	
B		KIT SERVICE PISTOL GRIP W/COLOR CLIPS	90040001	
C		KIT SERVICE 2.5" BALE W/COLOR CLIPS	90050001	
D		KIT SERVICE BALE AND PISTOL GRIP COLOR CLIPS ONLY	90070001	

* INSTALLED AT FACTORY FOR FINAL FLOW CALIBRATION.
 ** FOR OTHER AVAILABLE OPTIONS, INLET ADAPTERS AND KITS
 GO TO akronbrass.com - REFERENCE DOCUMENT 127762

PHONE: 330.264.5678 or 800.228.1161 | FAX: 330.264.2944 or 800.531.7335 | www.akronbrass.com

Parts List Sheet:

127270

WARRANTY AND DISCLAIMER*: We warrant Akron Brass products for a period of five (5) years* after purchase against defects in materials or workmanship. Akron Brass will repair or replace product which fails to satisfy this warranty. Repair or replacement shall be at the discretion of Akron Brass. Products must be promptly returned to Akron Brass for warranty service. We will not be responsible for: wear and tear; any improper installation, use, maintenance or storage; negligence of the owner or user; repair or modification after delivery; failure to follow our instructions or recommendations; or anything else beyond our control. **WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, OTHER THAN THOSE INCLUDED IN THIS WARRANTY STATEMENT, AND WE DISCLAIM ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.** Further, we will not be responsible for any consequential, incidental or indirect damages (including, but not limited to, any loss of profits) from any cause whatsoever. No person has authority to change this warranty. *Unless otherwise provided herein. Akron Brass industrial electronic components & the Severe-Duty Monitor have a one (1) year warranty. Select Akron Brass handline nozzles and valves carry a ten (10) year warranty. Scene Star Lights carry a (6) year warranty. Weldon products have a two (2) year warranty from date of manufacture (excluding consumable components). Select Weldon LED products carry a five (5) year warranty. Honda products have the manufacturers' warranty and Akron Brass disclaims any warranty in respect of those products.
 © 2016 Akron Brass Company. All rights reserved. No portion of this can be reproduced without the express written consent of the Akron Brass Company.