

677


ГĤ


.97

(1.75)(1.54)

\_

THIS DRAWING AND ALL INFORMATION CONTAINED HEREIN STHE PROPERTY OF WELDON TECHNOLOGIES INC: AND MAY NOT BE COPED, REPRODUCED, OR DEVILGED TO UNAUTHORIZED FERSIONS WITHOUT THE EXPRESS WITH TO CONSTN. OF WILDON TECHNOLOGIES, INC: AS IT & BRION PROVIDED SOLIEY TOR THE CONVENIENCE OF THE USER AND SHALL BE RETURNED TO WELDON TECHNOLOGIES, INC UPON REQUEST.





 REV.
 ECN #


 A
 R0628
 RELEA


 B
 0773
 REVISI

 C
 0773
 REVISI

REAR VIEW SHOWING S-MUX CONNECTORS & PIN NUMBERS

S-MUX CONNECTOR PIN ASSIGNMENTS MATING CONNECTOR / DEUTSCH - DTM06-4S	
PIN NUMBER	DESCRIPTION
1	S-MUX COMM A
2	S-MUX COMM B
3	GROUND
4	+12VDC





REQUIRED PANEL CUTOUT DIMENSIONS FOR SNAP-IN MOUNTING

## NOTES:

Α

D

- 1) GIVEN THE CUTOUT DIMENSIONS SHOWN ABOVE, MODULES MAY BE STACKED VERTICALLY NO CLOSER THAN 2.20 INCHES CENTER-TO-CENTER AND NO CLOSER THAN 5.07 INCHES CENTER-TO CENTER HORIZONTALLY.
- 2) CLEAR, ACRYLIC, KEY CAPS ARE SHIPPED WITH EACH MODULE TO ALLOW FOR THE INSTALLATION OF CUSTOM KEY LEGENDS. BLANK SHEETS OF LASER-PRINTABLE, KEY LEGENDS ARE AVAILABLE (WELDON P/N 0020-1736-00) WITH 88 DIE-CUT LEGENDS PER SHEET. AFTER THE APPROPRIATE LEGEND IS INSTALLED, SIMPLY PUSH THE CLEAR, KEY CAP OVER THE KEY.


CH.

-

-( 3.60 )--( 4.34 )- 5) MATING CONNECTOR IS A DEUTSCH P/N DTM06-4S.

6) SPECIFICATIONS: OPERATING TEMPERATURE RANGE IS -40 °C TO +85 °C OPERATING VOLTAGE RANGE IS +9 VDC TO +16 VDC.

7) MODULE-TO-MODULE WIRING IS ACCOMPLISHED WITH S-MUX CABLE, WELDON P/N 0L40-2088-00. FOR INFORMATION ON CABLE CONSTRUCTION SEE WELDON DOCUMENT C0L40-1950-00.



ISOMETRIC VIEW



D