

ISO 9001: 2000 Registered Company In U.S./International Weldon, a division of Akron Brass

PH: 614.529.7230 PH: 800.989.2718 FAX: 614.527.3547


3565 Paragon Drive Columbus, OH 43228

Vista IV Display

Control your lighting and HVAC with the full color Vista IV display. Now offering new features including: Optional Touch Screen with buttons, 800 x 480 resolution, Four Video Ports, Firmware update by USB. This display has a wide operating temperature range, Automatic Screen Switching in response to current conditions, Sleep Mode option to eliminate night glare. Available in panel mount or 6" arm mount.

- Touch screen option
- 800 x 480 resolution
- Four video ports
- Flash updates with USB memory stick
- Operates in 12V and 24V applications
- Virtual switches
- Display inside and outside temperature
- Automatic climate control
- 100% configurable (OEM level)
- Field re-programmable
- Peer to peer network
- \bullet On-board diagnostics \checkmark service information
- Colors change to indicate button status
- Improved sunlight readability
- Video ready for:
 - Backup camera / Thermal cameras
 - DVD - GPS

Model Number Configuration Guide



A= Cable Accessory (1 = none; 2 = 6" Video Pig Tail; 3 = 10" Pig Tail) B= Legend Button Colors (0=Red/Blue/Green; 1=Green/Blue/Green) C=Touch Screen Capable (0=No; 1=Yes) D=Finish/Enclosure (1=Standard)

E=Mounting Method (0=Panel Mount; 1=6" Arm Mount) XX=Legend Label (Contact your Akron Brass Sales Rep for a current list of available legends)

		Tim	er Menu	_			23:01
Caseldoon Diet Thip			ontelorem		ļ		entut Step
Countries. Cleve	1	00	3:00			10	
T Minute Timer			3:00				
S Minute Timer							
WELD	ON -		Hor	ne Me	Hnu		
WELD	<u>ON</u> -	23:01	Hon			2004	0.0 V
Warning Lts Heast	DVBAD	23:01	Monday		01	- w	0.0 V ork Lts Yienu
Warning Lts	DVBAD		Monday	3en	01	W	ork Lts
Warning Lts	DVBAD		Monday	3en	01	W	ork Lts Nenu gnostice

Gauges



LDON

A DIVISION OF AKRON BRASS

Touch Screen Option Now Available!







Flash Updates with USB memory stick

Technical Specifications:

Operating Voltage	9-32v (12 or 24V)	
Operating Temperature	-40°C to +85°C	
Electrical Protection	Load dump, jump start, reverse polarity, ESD, EMI/RFI	
Real-time Clock	Ten year retention	
Mating Connector:	1: Comm. Hi, 2: Comm. Lo,	
Deutsch DT06-4S	3: Ground, 4: Power	
Startup Time	< 3 seconds	

PH: 800.989.2718 Fax: 614.527.3547 www.weldoninc.com