

Akromatic 2000 Master Stream Nozzle

STYLE 5170

Designed for flows from 500 to 2000 gpm (1900-7600 lpm) - at an operating pressure of 80 psi (5.5 bar)


Features

Designed for flows from 500 to 2000 gpm (1900-7600 lpm) - at an operating pressure of 80 psi (5.5 bar)

- Pyrolite
- Manual Pattern Control
- 500-2000 gpm (1900-7600 lpm) flow - 500-1500 gpm (1900-5700 lpm)
- Optional flow
- 3 1/2" (89 mm) Inlet (NH OR NPSH ONLY)
- Fixed Teeth
- 9 1/8" (232 mm) long
- 15 -1/4 lbs. (7.0 kg)



Specifications

Style	5170
Warranty	
Weight	15 1/4 lbs (6.9 kg)
Type	Master Stream
Material	Pyrolite
Brand	Akromatic
Length	9 1/8" (232 mm)
Width	8 3/4" (223 mm)
Height	8 3/4" (223 mm)

Akromatic 2000 Master Stream Nozzle

STYLE 5170



Outdated bumper design, not compatible with 738 Foam Tube



Akromatic 2000 Master Stream Nozzle

STYLE 5170

Akromatic 2000 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that maintains a consistent pressure throughout a flow range of either 500 to 1500 gpm or 500 to 2000 gpm at 80 psi.