

Akromatic Hydraulic Master Stream Nozzle

STYLE 5056

This hydraulicly actuated nozzle is designed for flows from 350-1000 gpm (1325-3800 lpm) At 100 psi (7 bar) operating pressure.

Features

This hydraulicly actuated nozzle is designed for flows from 350-1000 gpm (1325-3800 lpm) At 100 psi (7 bar) operating pressure.

- Brass Nozzle
- Hydraulic Pattern Control
- 350-1000 gpm (1325-3800 lpm) flow
- 2 1/2" Inlet (65 mm)
- Spinning Teeth
- 9 3/4" long (248 mm)
- 30.5 lbs. (13.8 kg)



| Style | 5056 |
|----------|----------------------|
| Warranty | WARRANTY |
| Weight | 30 1/2 lbs (13.8 kg) |
| Туре | Master Stream |
| Material | Brass |
| Brand | Akromatic |
| Length | 9 3/4" (229 mm) |
| Width | 6" (153 mm) |
| Height | 11" (280 mm) |

Akromatic Hydraulic Master Stream Nozzle

STYLE 5056

Akromatic 1000 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that maintains a consistent pressure throughout a flow range of 350 to 1000 gpm. The nozzle shall have spinning teeth and have a 2 1/2" swivel base.