

Akromatic 1000 Hydraulic Master Stream Nozzle

STYLE 5055

This hydraulically actuated nozzle is designed for flows from 350-1000 gpm (1325-3800 lpm) At 100 psi (7 bar) operating pressure.

Features

This hydraulically actuated nozzle is designed for flows from 350-1000 gpm (1325-3800 lpm) At 100 psi (7 bar) operating pressure.

- Pyrolite Nozzle
- Hydraulic Pattern Control
- 350-1000 gpm (1325-3800 lpm) flow
- 2 1/2" Inlet (65 mm)
- Spinning Teeth
- 9 3/4" long (248 mm)
- 9.25 lbs. (4.2 kg)



Specifications

Style	5055
Warranty	
Country of Manufacture	
Weight	9 1/4 lbs (4.2 kg)
Type	Master Stream
Material	Pyrolite
Brand	Akromatic
Length	9 3/4" (248 mm)
Width	6" (153 mm)
Height	11" (280 mm)

Akromatic 1000 Hydraulic Master Stream Nozzle

STYLE 5055

Akromatic 1000 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that maintains a consistent pressure throughout a flow range of 350 to 1000 gpm. The nozzle shall have spinning teeth and have a 2 1/2" swivel base.