

Mid-Range Assault Tip

STYLE 4866

Assault Nozzles combine quality stream performance at a variety of pressures with the simplicity of a fixed orifice. Quality stream performance at a variety of pressures, combined with a durable and simple design makes it an unbeatable value. Available in many flow and pressure combinations ranging from 50 psi (3.5 bar) to 100 psi (7 bar) and from 95 gpm (360 lpm) to 200 gpm (750 lpm). Includes matching smoothbore flows at 50 psi (3.5 bar) of 161 and 185 (609, 700 lpm).

Find a distributor near you for information about this fixed orifice fire hose nozzle.

[Pair with a handline nozzle shutoff and ergonomic pistol grip. Choose from several "snap-on" grip and handle colors to help identify pre-connects and better manage inventory.](#)

Features

Akron Assault Nozzles combine quality stream performance at a variety of pressures with the simplicity of a fixed orifice. It is one of the most versatile and easy to use fixed orifice fire hose nozzles in today's fire service. Quality stream performance at a variety of pressures, combined with a durable and simple design makes the Assault an unbeatable value.

The Assault provides:



- Better stream performance at pressures as low as 50 PSI
- Affordably priced
- Simplified nozzle training
- No recalibration required
- Low maintenance due to simple, durable design

Features:

- Pattern Identification
- Enhanced flow characteristics on 2 1/2" Assaults (deeper throat design)
- Larger easy to read labels
- Easy to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Meets European Standard
- Quick change pattern adjustment
- Specify Pressure and Flow
- Compatible with Quick-Attack Foam Tube Style 796
- 1 1/2" (38 mm) Swivel Inlet



Specifications

Style	4866
Certification(s)	
Warranty	
Weight	2 3/4 lbs (1.2 kg)
Type	Fixed Orifice
Material	Pyrolite
Brand	Assault
Swivel Inlet	1 1/2" (38 mm)
Length	6 1/2" (165 mm)
Flow (GPM)	95, 125, 150, 175, 200 @ 100 PSI -- 125, 150, 175, 200 @ 75 PSI -- 150, 161, 175, 185 @ 50 PSI
Flow (LPM)	360, 475, 550, 660, 750 @ 7 BAR -- 475, 550, 660, 750 @ 5 BAR -- 550, 610, 660, 700 @ 3.5 BAR

- 6 1/2" (165 mm) Long
- 2.75 lbs. (1.2 kg)

Applications/Solutions

- Fire OEMs
- Firefighting - Airport (ARFF)
- Firefighting - Industrial
- Firefighting - Structural
- Firefighting - Wildland Forestry



Mid-Range Assault Tip

STYLE 4866



Mid-Range Assault Tip

STYLE 4866

A combination straight stream and fog tip, Akron Brass Style 4866 Mid-Range Assault Tip with Spinning teeth shall have the following: quick change stream pattern identification, ¼ turn bumper from straight stream to fog, raised bumper lug marks straight stream, compatible with Akron Brass Style 796 Quick-Attack Foam Tube, available in the following flow (insert flow) and pressure (insert pressure), shall be 6-1/2" (165 mm) long, and weight 2.75 pounds (1.2 kg), and shall include a 1-1/2" (38 mm) or 2-1/2" (65 mm) swivel inlet for attachment to a hose or shutoff. Tip shall have a minimum of 100 degree fog, a 10 year warranty and meet NFPA 1964.