

2 1/2" High Range Assault Nozzle with or without Pistol Grip

STYLE 4826

Assault Nozzles have quality stream performance at a variety of pressures and flows with the simplicity of a fixed orifice, combined with a durable and simple design. It is one of the most versatile and easy-to-use nozzles in today's fire service.

[Find an Akron Brass distributor](#) near you for more information about this High Range nozzle.

[Choose from several "snap-on" grip and handle colors to help identify pre-connects and better manage inventory.](#)



Features

The Assault High Range nozzle provides:


- Quality stream performance at pressures as low as 50 PSI
- Affordably priced
- Simplified nozzle training
- No recalibration required
- Low maintenance due to simple, durable design

Features:

- Pattern Identification
- Enhanced flow characteristics with a deeper throat design
- Easy to read labels
- Easy to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Specific models FM approved (contact Akron Brass for more information)
- Quick change pattern adjustment
- Specify Pressure and Flow
- Nozzle is standard with Pistol Grip and Spinning Teeth
- Swivel 1-1/2" (38 mm) & 2-1/2" (65 mm) Inlet, also available with ZT (Zero Torque)
- 12-1/8" (206 mm) Long
- 7-5/8 lbs. (3.5 kg)

Applications/Solutions

Specifications

Style	4826
Certification(s)	 
Warranty	
Weight	7 5/8 lbs (3.5 kg)
Type	Fixed Orifice
Material	Pyrolite
Brand	Assault
Swivel Inlet	2 1/2" (65 mm)
Length	12 1/8" (206 mm)
Flow (GPM)	200, 250, 300, 350 @ 100 PSI -- 200, 250, 300 @ 75 PSI -- 210, 250 @ 50 PSI
Flow (LPM)	750, 950, 1140, 1325 @ 7 BAR -- 750, 950, 1140 @ 5 BAR -- 795, 950 @ 3.5 BAR

- Equipment and Tank Washing
- Fire OEMs
- Firefighting - Airport (ARFF)
- Firefighting - Industrial
- Firefighting - Structural
- Firefighting - Wildland Forestry



2 1/2" High Range Assault Nozzle with or without Pistol Grip

STYLE 4826

