AkroFoam Master Stream Nozzle with Pickup Tube

STYLE 4475

The AkroFoam foam nozzles are self-educting master stream nozzles designed for educting foam at flow rates up to 1000 gpm (4800 lpm). Contact a distributor today for more information about our master stream foam nozzles.

Features

AkroFoam foam nozzles have the following features:

- Manual Pattern Control

- Spring loaded baffle that allow flow setting selection of 350, 500, 750, or 1000 gpm (1325, 1900, 2900, or 3800 lpm) with a simple push and turn of the baffle head.

- Quick connect, adjustable metering head with pick up rates 1% & 3%, plus 6% for 350 & 500 gpm (1325 & 1900 lpm) and 1% & 3% for 750 & 1000gpm (2900 & 3800 lpm)

-Integrated Foam Shutoff

Specifications

Style	4475
Warranty	
Weight	12 lbs (5.4 kg)
Туре	Foam
Material	Pyrolite
Brand	AkroFoam
Swivel Inlet	2 1/2" (65 mm)
Length	10 7/8" (276 mm)
Width	11" (280 mm)
Height	9 1/4" (235 mm)
Flow (GPM)	350-500-750-1000
Flow (LPM)	1325-1900-2900-3800

1.800.228.1161 | akronbrass.com | akroncare@idexcorp.com





AkroFoam Master Stream Nozzle with Pickup Tube

STYLE 4475





Style 4475 AkroFoam (with old control ring)

