

Wide-Range Turbojet Nozzle with or without Pistol Grip

STYLE 1763

The Turbojet is a constant gallonage nozzle (flow remains the same in all patterns) with multiple flow settings for operator flow control. Use the Turbojet one time and see why it's the nozzle of choice by firefighters worldwide.

Unless otherwise specified on purchase order, nozzle will be shipped with attached Pistol Grip.

[Choose from several "snap-on" grip and handle colors to help identify pre-connects and better manage inventory.](#)



Features

Wide-Range Turbojet Nozzles Features:

- Pattern Identification
- Larger more legible labels
- Simple to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Meets European Standard
- Flow setting up to 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Compatible with Quick-Attack Foam Tube Style 796
- Replacement for style 1762 Turbojet nozzle

Applications/Solutions

- Firefighting - Airport (ARFF)
- Firefighting - Industrial
- Firefighting - Structural
- Firefighting - Wildland Forestry
- Marine
- Mining



Specifications

Style	1763
Certification(s)	 
Warranty	
Weight	5 3/4 lbs (2.6 kg)
Type	Selectable Gallonage
Material	Pyrolite
Brand	TurboJet
Swivel Inlet	1 1/2", Optional 2 1/2" (38 mm, Optional 65 mm)
Length	11" (279 mm)

Wide-Range Turbojet Nozzle with or without Pistol Grip

STYLE 1763



Wide-Range Turbojet Nozzle with or without Pistol Grip

STYLE 1763

Wide-Range Turbojet Nozzle Specifications

Lightweight fog and straight stream nozzle with multiple fixed constant gallonage settings of 30-95-125-150-200 gpm (115-360-475-550-750 lpm) @ 100 or 75 psi (7 or 5 bar). The nozzle shall have spinning teeth, multiple pattern detents, a one piece solid rubber-like handle with dual handle stops, dual drive trunnions, pistol grip and an extruded Pyrolite body. The nozzle shall also have a minimum 110° angle at wide fog, a full-time swivel inlet, come with a ten year warranty, be capable of flushing without shutting down. Must meet all aspects of NFPA 1964 with test results available.