

## Mid-Range Turbojet Tip - DISCONTINUED

### STYLE 1737

### Discontinued effective January 2024

The Turbojet is a constant gallonage nozzle (flow remains the same in all patterns) with multiple flow settings for operator flow control. Use the Turbojet one time and see why it's the nozzle of choice by firefighters worldwide.

[Pair with a handline nozzle shutoff and ergonomic pistol grip. Choose from several "snap-on" grip and handle colors to help identify pre-connects and better manage inventory.](#)

### Features

Mid-Range Turbojet Tip Features:

- Pattern Identification
- Larger more legible labels
- Simple to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Meets European Standard
- Flow settings at 100 psi (7 bar) standard, 75 psi (5 bar) optional
- Replacement for style 1724 Turbojet tip
- Compatible with Quick-Attack Foam Tube Style 793

### Applications/Solutions

- Mining



### Specifications

Style	1737
Warranty	
Weight	4 1/2 lbs (2.0 kg)
Type	Selectable Gallonage
Material	Pyrolite
Brand	TurboJet
Swivel Inlet	1 1/2" (38 mm)
Length	7-1/4" without inlet (152 mm)

## Mid-Range Turbojet Tip - DISCONTINUED

STYLE 1737



Shown with 2127



Shown with 2127



# Mid-Range Turbojet Tip - DISCONTINUED

## STYLE 1737

Lightweight fog and straight stream Style 1737 Mid-Range TurboJet tip with multiple fixed constant gallonage settings of 95-125-150-200 gpm (360-475-550-750 lpm) @ 100 or 75 psi (7 or 5 bar). The nozzle shall have spinning teeth, multiple pattern detents, and an extruded Pyrolite body. The nozzle shall also have a minimum 110° angle at wide fog, a full-time swivel inlet, come with a ten year warranty, be capable of flushing without shutting down. Must meet all aspects of NFPA 1964 with test results available.