

# 2 1/2" High-Range Turbojet Break apart Nozzle with Pistol Grip

## STYLE 1736

The Turbojet is a constant gallonage nozzle (flow remains the same in all patterns) with multiple flow settings for operator flow control. Use the Turbojet one time and see why it's the nozzle of choice by firefighters worldwide.



### Features

High-Range Turbojet Nozzles Features:



- Pattern Identification
- Larger more legible labels
- Simple to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Meets European Standard
- Flow setting up to 250 GPM (950 LPM) at 100 psi (& bar) standard, 75 psi (5 bar) optional
- Compatible with Quick-Attack Foam Tube Style 770
- Combination of Style 1727 tip + Style 2126 Shutoff with Pistol Grip

### Applications/Solutions

- Mining



### Specifications

Style	1736
Certification(s)	
Warranty	
Weight	7 3/8 lbs (3.3 kg)
Type	Selectable Gallonage
Material	Pyrolite
Brand	TurboJet
Swivel Inlet	2 1/2" (65 mm)
Length	12 3/4" (324 mm)

# 2 1/2" High-Range Turbojet Break apart Nozzle with Pistol Grip

STYLE 1736



# 2 1/2" High-Range Turbojet Break apart Nozzle with Pistol Grip

**STYLE 1736**

## **Turbojet Nozzle Specifications**

Lightweight fog and straight stream nozzle with multiple fixed constant gallonage settings. The nozzle shall have spinning teeth, multiple pattern detents, a one piece solid rubber-like handle with dual handle stops, dual drive trunnions and an extruded Pyrolite body. The nozzle shall also have a minimum 110° angle at wide fog, a full-time swivel inlet, come with a ten year warranty, be capable of flushing without shutting down. Must meet all aspects of NFPA 1964 with test results available.