

Turbojet Tip

STYLE 1703

The Turbojet is a constant gallonage nozzle (flow remains the same in all patterns) with multiple flow settings for operator flow control. Use the Turbojet one time and see why it's the nozzle of choice by firefighters worldwide.

[Pair with a handline nozzle shutoff and ergonomic pistol grip. Choose from several "snap-on" grip and handle colors to help identify pre-connects and better manage inventory.](#)

Features

Features:

- Pattern Identification
- Larger more legible labels
- Simple to operate (1/4 turn from straight stream to fog)
- Raised lug marks straight stream for limited visibility operations
- Easy to service & repair
- Meets European Standard
- Flow setting at 100 psi (7 bar) operating pressure (230 psi (16 bar) maximum operating pressure)
- Raised bumper lug for straight stream pattern identification
- Compatible with Quick-Attack Foam Tube Style 790
- For use on Style 753 shutoff

Applications/Solutions

- Mining



Specifications

Style	1703
Certification(s)	
Warranty	
Weight	1 3/4 lbs (.8 kg)
Type	Selectable Gallonage
Material	Pyrolite
Brand	TurboJet
Swivel Inlet	1.5 (38 mm)
Length	6 5/8" (14 mm)
Flow (LPM)	50-100-150-230



Turbojet Tip

STYLE 1703



Turbojet Tip

STYLE 1703

An Akron Brass Turbojet lightweight fog and straight stream tip Style 1703 with multiple fixed constant gallonage settings of 13-25-40-60 GPM (50-100-150-230 lpm) at 100 psi (7bar) shall be provided. The tip shall have spinning teeth, multiple pattern detents, a rubber bumper with raised lug for pattern identification, and extruded Pyrolite body and sleeve. The tip shall also have a minimum 110° angle at wide fog, a 1.5”(38 mm) swivel inlet, be capable of flushing without shutting down, and must meet all aspects of NFPA 1964 with test results available.