

# 95 GPM Portable By-Pass Eductor

## STYLE 3097


The Akron By-Pass Eductor utilize a built-in by-pass chamber, allowing the operator to change from water to foam without shutting down and feature a large, easy to read, and removable metering dial with settings between 0% and 6%. The Eductors are rated to flow at 200 psi (14 bar) inlet pressure and work effectively with nozzles rated from 50 to 100 psi (3 to 7 bar).

## Features

- Built-in by-pass chamber, allows the operator to change from water to foam without shutting down
- Large, easy to read, and removable metering dial with settings between 0% and 6%. Detents at 1/4, 1/2, 1, 3 and 6%
- Rated to 95 gpm (360 lpm) at 200 psi (14 bar) inlet pressure
- Works effectively with nozzles rated from 50 to 100 psi (3 to 7 bar)
- 1 1/2" (38 mm) or 2 1/2" (65 mm) swivel inlet x 1 1/2" (38mm) male
- Brass construction with chrome trim
- 8 quick-change handle positions with a Swing-Out Valve handle
- Optional pipe thread connections available for truck plumbing



## Specifications

Style	3097
Warranty	
Country of Manufacture	
Type	Eductors
Material	Brass

# 95 GPM Portable By-Pass Eductor

STYLE 3097

Foam Eductor Metering Head

