

FireFox Nozzle (350-400-450-500GPM)

STYLE 3293

An electrically controlled nozzle with flows from 350 to 500 gpm (1325 to 1900 lpm) at an operating pressure of 100 psi (7 bar). The FireFox nozzle comes with either a single fixed flow baffle or an adjustable four setting baffle and is for use with 12 or 24 Volt monitors featuring current limiting, such as the Style 3463 FireFox.

Features

FireFox Electric Nozzle • 2 1/2" swivel inlet for flows 350 to 500 gpm • Spinning teeth • Optional flat disperse pattern - Must specify • Optional add-on foam tubes • Adjustable Flow Options: - 350-400-450-500 gpm (1330-1525-1700-1800 lpm) - Optional 500, 1000, 1500, 2000 LPM settings • Fixed Flow Options: (Must specify flow rate and pressure)

Applications/Solutions

- Deicing
- Firefighting - Airport (ARFF)
- Firefighting - Structural
- Firefighting - Wildland Forestry
- Specialty Vehicles



Specifications

Style	3293
Certification(s)	
Warranty	
Weight	7 1/2 lbs (3.4 kg)
Brand	FireFox
Swivel Inlet	2.5" (65 mm)
Length	7 3/7" (187 mm)
Flow (GPM)	350-400-450-500
Flow (LPM)	1325-1525-1700-1800



FireFox Nozzle (350-400-450-500GPM)

STYLE 3293

Style 3293

