

1 1/2" ProVenger FG Fire Hose Nozzle with pistol grip - DISCONTINUED

STYLE 4116

Discontinued effective January 2024

The 1 1/2" ProVenger FG is the fixed gallonage style for the ProVenger Series Nozzles. ProVenger nozzles provide great stream quality and a simple design to give you the value you expect from Akron Brass.

Find an Akron Brass distributor near you for more information about this fire hose nozzle.

Features

- Great stream performance
- Simplified nozzle training
- Affordably priced
- Standard swivel inlet 1 1/2" NH (38 mm), additional inlet types available
- Easy to operate
- 150 gpm (550 lpm) @ 75 or 100 psi (5 or 7 bar)
- Also available in 60-95-125- or 150 gpm (230-360-475-or 550 lpm) @ 75 or 100 psi (5, or 7 bar)
- Raised lug marks straight stream for limited visibility operations
- Quick change pattern adjustment

Applications/Solutions

- Fire OEMs
- Firefighting - Airport (ARFF)
- Firefighting - Industrial
- Firefighting - Structural
- Firefighting - Wildland Forestry



Specifications

Style	4116
Certification(s)	 
Warranty	
Weight	4.3 lbs (2 kg)
Material	Pyrolite
Brand	ProVenger
Swivel Inlet	Standard 1 1/2" or 2 1/2" NH, additional inlet types available (38 mm, 65 mm)
Length	11" (280 mm)
Height	9 -1/8" (232 mm)
Flow (GPM)	60-95-125-150 GPM
Flow (LPM)	230-360-475-550 LPM
Orifice Optional	Fixed Orifice



1 1/2" ProVenger FG Fire Hose Nozzle with pistol grip - DISCONTINUED

STYLE 4116

Provenger Nozzle with BIM Inlet



1 1/2" ProVenger FG Fire Hose Nozzle with pistol grip - DISCONTINUED

STYLE 4116

Style 4116 (Fixed gallonage)

Lightweight fog and straight stream nozzle with fixed constant gallonage settings labeled on the baffle head. Nozzle shall have spinning turbine teeth, multiple pattern detents, a one-piece solid nylon reinforced bumper, one-piece solid rubber-like handle with dual stops, dual drive trunnions, and an extruded single piece Pyrolite body. The nozzle also shall have a minimum 100° fog pattern, a fulltime swivel inlet, be capable of flushing without shutting down, and a 5 year warranty. Must meet all aspects of NFPA 1964 with test results available.