

## Akrofoam 2000 GPM

### STYLE 4478


The Akrofoam nozzles are self-educing master stream nozzles designed for educating foam at flow rates up to 2000 gpm (7600 lpm).

#### Features

- Spring loaded baffle that allows flow setting selection of 750, 1000, 1500, or 2000 gpm (2900, 3800, 5700, or 7600 lpm) with a simple push and turn of the baffle head
- Quick connect, adjustable metering head with pick up rates 1%, 3% and 6% for 750 and 1000 gpm (2900 and 3800 lpm) and 1% & 3% for 1500 and 2000 gpm (5700 and 7600 lpm)
- Orifices store conveniently on the nozzle for easy change of pickup rate and storage when not in use
- 3-1/2" NH inlet
- NFPA 1901 and 1964
- Operating pressure -100 psi (7 bars)
- Maximum Operating - 200 psi (13.8 bars)
- Weight - 17.4 lbs (8 kg)



#### Specifications

Style	4478
Certification(s)	
Weight	17.4 lbs (8 kg)
Brand	AkroFoam
Swivel Inlet	3-1/2"
Length	6-5/16" (160 mm)
Width	10" (254 mm)
Height	13-3/4" (350 mm)
Inlet	3-1/2"

# Akrofoam 2000 GPM

STYLE 4478



# Akrofoam 2000 GPM

## STYLE 4478

A Combination fog and straight stream constant gallonage nozzle with four flow settings – 750, 1000, 1500, and 2000 gpm (2900, 3800, 5700, and 7600 lpm) shall be provided. Flow settings shall be capable of being changed by the rotation of the spring loaded baffle head. The nozzle shall have a 3.5" (89 mm) swivel inlet, storage of the foam orifice plates located on the nozzle. The nozzle shall have the option of a 10' (3 m) CAM lock quick disconnect foam pick up hose, a CAM lock cap for the foam pick up port, and a foam metering valve with foam shutoff. The nozzle shall be constructed of durable, lightweight Pyrolite with a weight less than 17.5 lbs. (7.94 kg) and a maximum length of 13.75" (322 mm).