1080S Warning Lamp, Stainless, Hal, Amber

STYLE 1080S-1100-20

-Original vehicle warning lights equipment for major school bus builders
-Body ground (-1100) or wire ground (-1106) versions
-Flat-back design allows surface mounting (no clearance holes to cut) and provides a large gasketed sealing area to vehicle
-Utilizes standard H3-55W bulb

Specifications

Style	1080S-1100-20
Country of Manufacture	
Depth	2.0 in (50.8 mm)
Diameter	7 in (178 mm)
Carton Quantity	36
Wattage	55
Volts	12.8
Amperage	4.6

Features

These 7” diameter warning lights surface mount to a vertical, planar vehicle surface using 4 customer supplied #8 or #10 screws on a 6.25” bolt circle. The vehicle warning light includes a 10mm thick closed cell foam pad that compresses to seal between the lamp body and the mounting surface. Wire exit into the vehicle must be placed so that lead wires can pass directly from the lamp through the mounting surface without being pinched. All holes for passing wires must use a protective grommet. - Enhanced corrosion resistant lamp back / 304 stainless steel - 3 year warranty on lamp back

1.800.228.1161 | www.weldoninc.com | weldoncare@idexcorp.com

Copyright 2024 Akron Brass Company. All rights reserved. No portion of this can be reproduced without the express written consent of the Akron Brass Company. (03/24)

1080S Warning Lamp, Stainless, Hal, Amber

STYLE 1080S-1100-20

The lamp complies with SAE J887 and all associated weathering tests as required by FMVSS108 for pupil warning lamps. An H3-55W halogen bulb along with a metalized reflector and specific optical lens combine to meet the photometric requirements of J887. Lamp mounting torque is recommended from 12 to 20 in-lbs. Exceeding 20 in-lbs can deform the lamp’s steel housing and create a leak path.