

Akrofoam 2000 GPM Pyrolite Nozzle with Electric Pattern Actuation

STYLE 4479

The Akrofoam nozzles are self-educing master stream nozzles designed for educating foam at flow rates up to 2000 gpm (7600 lpm).

Features

- Spring loaded baffle that allows flow setting selection of 750, 1000, 1500, or 2000 gpm (2900, 3800, 5700, or 7600 lpm) with a simple push and turn of the baffle head
- Quick connect, adjustable metering head with pick up rates 1%, 3% and 6% for 750 and 1000 gpm (2900 and 3800 lpm) and 1% & 3% for 1500 and 2000 gpm (5700 and 7600 lpm)
- Orifices store conveniently on the nozzle for easy change of pickup rate and storage when not in use
- 3-1/2" NH inlet
- NFPA 1901 and 1964
- Operating pressure -100 psi (7 bars)
- Maximum Operating - 200 psi (13.8 bars)
- Weight - 17.4 lbs (8 kg)



Specifications

Style	4479
Certification(s)	
Country of Manufacture	United States
Weight	17.4 lbs (8 kg)
Brand	AkroFoam
Swivel Inlet	3-1/2"
Length	6-5/16" (160 mm)
Width	10" (254 mm)
Height	13-3/4" (350 mm)
Inlet	3-1/2"



Akrofoam 2000 GPM Pyrolite Nozzle with Electric Pattern Actuation

STYLE 4479

